

LMS Video Surveillance Systems

Wi-Fi IP Indoor & Outdoor Cameras



See your premises online with wireless 802.11 cameras

LMS Video Surveillance System's newest solution!

- ✓ Highest resolution remote video on the market! 25 frames per second @ VGA res. (640x480)
- ✓ Patented auto-detect and enrollment of wireless cameras- true plug-n-play
- ✓ Choice of Wi-Fi Cameras, pan & tilt, outdoor/waterproof or fixed IP, in all-inclusive turnkey kits
- ✓ Put live video of you premises in the palm of your hands with iPhones, Blackberrys, etc, or on a computer, and send video alerts anywhere in the world.



LMS Video Surveillance Systems

Wi-Fi IP Indoor & Outdoor Cameras



IP Camera	Wireless Fixed IP	Wireless Pan/Tilt IP	Outdoor Wireless Fixed IP
Model	FIXEDCAM	PTCAM	OUTCAM
Starter Kit	KIT1	KIT2	KIT3
Video Image Sensor	Ominivision 7725 CMOS, 1/6" VGA Resolution	1/4" CMOS, VGA Resolution	1/5" CMOS, VGA Resolution
Lens:	F2.8 Fixed Focus, Effective Range: 0.2M to infinity	F2.0 Fixed Focus, Effective Range : 50cm to infinity	F2.0 Fixed Focus, Effective Range: 0.2M to infinity
Compression	MPEG-4	MPEG-4	MPEG-4
Resolution Support	640x480	640 x 480	640x480
Frame Rate, in VGA	30 fps	30 fps	30 fps
Image Control	AWB, Brightness	AWB, AGC, Sharpness, Brightness	AWB, AGC, Contrast, Brightness
Video options	Motion-Detection, Time Stamp, Text Overlay	Motion-Detection, Time Stamp, Text Overlay	Motion-Detection, Time Stamp, Text Overlay
Pan/Tilt Range		Pan: 126°, Tilt 64° + 53° View Angle, respectively	
Audio	Bi-directional audio, built-in Mic and ext. speaker connection	Bi-directional audio, built-in Mic and external speaker connection	Built in Microphone/Speaker. Bi-directional audio.
E-mail notification triggered by motion detection	Yes	Yes	Yes
Simultaneous Users	5	5	5
Wireless Standard	IEEE 802.11b and 802.11g	IEEE 802.11b and 802.11g	IEEE 802.11b and 802.11g
Range Indoor	50m	50m	50m
Outdoor rating			IP65 Waterproof rating
Infrared LEDs			8 IR LEDs with photoelectric cell control; Night Vision Filter
Encryptions	WPA, WPA2, 128bit WEP	WPA, WPA2, 128bit WEP	H.264, WPA, WPA2, 128bit WEP
NAPCO Automatic Secure Enrollment (Pats. Pending)	Yes	Yes	Yes
Working Temperature	-5C to + 50C	-5C to + 50C	-0C to + 50C
Power Adapter	5V / 2A, 100 / 240 VAC	5V / 2A, 100 / 240 VAC	5V/1A, 100/240 VAC
Certification	CE / FCC	CE / FCC	CE / FCC
Dimensions (HxWxD)	3.8 x 3.5 x 1.4"	5.7" x 3.8" x 3.1"	3.8" x 3.5" x 1.4"

iSeeVideo Wireless Cameras/Kits

Complete Wireless Camera Kit: One (1) 802.11 Wireless Fixed Camera, 640x480 hi-res, power adapter, Patented automatic-enroller Wireless Access Point (WAP) Module & power adapter.

Complete Wireless P/T Camera Kit: One (1) 802.11 Wireless Pan/Tilt Camera, 640x480 hi-res, power adapter, Patented automatic-enroller Wireless Access Point (WAP) Module & power adapter.

Complete Wireless Outdoor Camera Kit: One (1) 802.11 Wireless Weatherproof (IP65) Fixed Camera, 640x480 hi-res, with built-in PIR motion detector, 6 IR LEDs with photo cell activation and night vision filter, power adapter, Patented automatic-enroller Wireless Access Point (WAP) Module & power adapter.

Add-on 802.11 Wireless Fixed Camera: 640x480 hi-res AC transformer (Kits support up to 6 cameras).

Add-on 802.11 Wireless Pan/Tilt Camera: 640x480 hi-res, power adapter (Kits support up to 6 cameras).

Add-on Outdoor 802.11 Camera: Wireless Weatherproof (IP65) Fixed Camera, 640x480 hi-res, with built-in PIR motion detector, 6 IR LEDs with photo cell activation and night vision filter, power adapter. (Kits support up to 6 cameras).

Optional - Internet Video Recorder: Provides full-time hi-res recording of up to 6 cameras for 30 day (640x480). (Fewer cameras equates to even more storage time.)



Lawton Media Services LLC 203 421-5533

Specifications subject to change.